

ACS SERIES

# STATIONARY COMPACTOR



Galfab's stationary compactors are ideal for dry waste applications often found in distribution centers, office complexes, malls, department stores, and discount stores. These compactors are ideal to cost-effectively reduce waste to a fraction of its original size and maximize payload.

# OPTIONAL FEATURES

- Multi-Cycle Time
- Sonaizaire Door Control System
- Oil Heater
- Low Oil Shut Down
- AR 400 Floor
- Overall Run Time
- Low Temp Oil
- Breaker Bar Teeth
- Remote Control
- Biometric Access Control
- Guide Rails
- 24 Volt Control
- Steel Options-Open Hopper, Walk Up, Walk On, Chute Feed, Cart Tipper, Total Enclosures

# ACS SERIES MODELS

Item	ACS200	ACS200HD	ACS300	ACS300HD
Overall Height	48"	48"	48"	48"
Overall Width	74"	74"	74"	74"
Overall Length	120"	120"	180"	180"
Charge Box Width	60"	60"	60"	60"
Charge Box Length	44.5"	44.5"	70.5"	70.5"
Discharge Height	34"	34"	34"	34"
Ground Height	14"	14"	14"	14"
Charge Box Capacity (Yards)	2	2	3	3
Clear Top Opening (LxW)	44.5" x 58"	44.5" x 58"	67.5" x 58"	67.5" x 58"
Cycle Time (sec)	69	60	68	60
Normal Force (lbs)	52,307	60,789	52,307	60,789
Maximum Force (lbs)	60,789	67,858	60,789	67,858
Ram Penetration (in)	14"	14"	12"	12"
Motor (HP)	10	10	15	15
Control Voltage (VAC)	110	110	110	110
Panel Box	NEMA 4	NEMA 4	NEMA 4	NEMA 4
Standard Controls	Start/Stop/Reverse	Start/Stop/Reverse	Start/Stop/Reverse	Start/Stop/Reverse
Power Unit UI Listed	Yes	Yes	Yes	Yes
Pump (GPM)	11	11	11	11
Normal Pressure (PSI)	1,850	2,150	1,850	2,150
Maximum Pressure (PSI)	2,150	2,400	2,150	2,400
Cylinder (in)	6x2.5	6x4	6x3	6x4
Weight (lbs)	4,550	4,870	6,000	6,310