

NEX SERIES

HD EXTENDIBLE TAIL HOIST



The Galfab NEX Series hoist is capable of handling heavier loads (60,000 and 75,000 lb. capacity) and is great for scrap applications. NEX Series hoists feature a solid 10" mainframe, a low 48 degree dump angle, standard inside controls and extremely durable rear hinge.

THE GALFAB ADVANTAGE



Outboard Supported Side Rollers

Greasable Roller shaft is removable with two bolts for ease of replacement and maintenance.



Wear Strips

Wear Strips add strength to the hoist mainframe and this extra layer of steel protects the mainframe from wear and scuffing when loading and unloading containers.



Lowest Loading Angle

Low loading angle is great for areas with low overhead and loading containers with loose debris.



80" Extendible Tail

80" Extendible tail gives your container added support while not losing your 48 degree dump angle.

STANDARD FEATURES

- 10" x 4" x 3/8" Main Frame Tube
- 1/2 inch x 3 1/2 inch Wear Strip on Top
- 1/2" x 4 inch Stiffener on the Bottom of the Main Frame
- No Sub Frame
- All Working Points Greaseable
- 2 1/2" Diameter Rear Hinge
- Pintle Ready Apron
- Auto Fold Forward DOT Bumper
- 1" Spring Loaded Container Locks
- 2 1/2" Diameter Lift Cylinder Shafts
- 12" Diameter Vertical Sheave and 10" Horizontal Sheaves
- 3/8 inch x 3 inch Winch Cylinder Rod Covers
- 6 Inboard and Outboard Supported Outside Rollers
- Container Long Sill Supports on Rear of Hoist Mainframe
- 48 Gallon Oil Reservoir with Sight and Temperature Gauge

- 25 Micron Filtration
- Inside and Outside Controls
- LED Lighting System
- Choice of Forward or Reverse Mount Single Stage or Telescopic Lift Cylinders
- 7/8" Cable with Heavy Duty Swivel Eye Hook
- 80 inch Extendible Tail
- No DOT Bumper
- Container Long Sill Supports
- Front Mount Pump
- Hoist Up Warning Light
- Sealed Wiring System
- Hoist Up Alarm
- Backup Alarm

OPTIONAL FEATURES

- "The Hooker" Hold On System
- Auxiliary Stops
- Work Lights
- Behind Cab and Oversize Oil Tanks
- Tool Boxes
- Poly or Steel Fenders
- Aluminum Fenders
- Tarping Systems
- Ratchet Tie Down Straps
- Pintle Hook
- Front Mount Pump
- PTO
- Drop Shaft
- On-Board Scale Systems
- Rear View Camera Systems
- Integrated hydraulics can be used, if hydraulic tarping system is used



"The Hooker"
Container Securement
System



Auxillary fold down
stops



Hydraulic Reservoirs



Tool Boxes



Poly, Steel & Aluminum
Fenders

Shop all replacement parts at:

[Galfab.com](https://www.galfab.com)



NEX SERIES MODELS

Model	Capacity	CA	CA with tarp	Length	Dump Angle Tail Retracted	Dump Angle Tail Extended	Up (sec)*	Down (sec)*	On (sec)*	Off (sec)*	Lift Cylinder	Winch Cylinder	Container Length ft	Apx Weight lbs
NEX60174S072	60,000	174"	186"	19' 10"	48°	28°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
NEX60174S072R	60,000	174"	186"	19' 10"	48°	28°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
NEX60174T121	60,000	174"	186"	19' 10"	48°	28°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7,225
NEX75174S072F7	75,000	174"	186"	19' 10"	48°	28°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
NEX75174S072R7	75,000	174"	186"	19' 10"	48°	28°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
NEX75174T121	75,000	174"	186"	19' 10"	48°	28°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7,350
NEX60194S072	60,000	194"	206"	22' 4"	48°	28°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
NEX60194S072R	60,000	194"	206"	22' 4"	48°	28°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
NEX60194T121	60,000	194"	206"	22' 4"	48°	28°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8,075
NEX75194S072F7	75,000	194"	206"	22' 4"	48°	28°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
NEX75194S072R7	75,000	194"	206"	22' 4"	48°	28°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
NEX75194T121	75,000	194"	206"	22' 4"	48°	28°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8,075

* Cycle Times are Factory developed and controlled by PTO output, oil viscosity, human and mechanical efficiency, and may vary accordingly.

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse, or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

