



BIG JOBS IN SMALL SPACES

When space is limited, turn to the GALFAB “MINI Series” stationary compactor – the packer that is designed to do BIG jobs in tight spaces such as trash and recycling rooms of office and residential high-rise buildings as well as apartments requiring chute fed applications. Moreover, when you need a ground level, manual feed compactor, the GF03 is also your solution!

This space-saving power-packer provides more compaction pressure with its energy-saving 3HP motor than most competitors’ 5HP motor models. Also, you don’t need to bring in expensive power because you can elect to run this powerful little compactor using 110 volt power and not sacrifice its packing ability which is just another winning feature.



GF03 MINI STATIONARY COMPACTOR

Single Side Latch System whereby the container is easily detached from the compactor by simply raising a single handle, thereby saving both space and time.

STANDARD FEATURES

- 2 Cubic Yard Compactor
- 6" x 2" x 1/4" Long Sills
- Sealed Rear Door
- Double End Pick Up
- Double Articulating Hinge
- 3" Channel Cross Sills
- Solid Steel Nose Cones
- 3/8" AR Plate Compactor Floor
- 7 Ga. Floor and Sides
- 10 Ga. Roof
- 6 1/2" Ram Penetration

DIMENSIONS

Item	Description
WASTEC Rating	.24 Cubic Yards
Mfrs. Rated	.33 Cubic Yards
Cleartop Opening	22.5" x 28" x 24" Deep
Ram Penetration	6"
Cylinder Size	2 – 2.5" x 20"
Compactor Sides	.31 Plate
Ram Top	.38 Plate
Ram Face	.38 Plate
Power Pack HP	3 HP 3 Phase (or) 1 P Single Phase
Norm. Force	15,500 lbs
Max. Force	17,500 lbs
Norm. Ram Face Pressure	31.3 PSI
Max. Ram Face Pressure	35.4 PSI

OPTIONAL FEATURES

- 6" x 2" x 3/8" Long Sills
- Low Profile Compactor
- Sliding Door Hinge
- Roller Options
- Power Unit

STANDARD POWER PACK

Item	Description
Hydraulic Pump	5 GPM 2-stage (3 HP) / 3 GPM 2-stage (1 HP)
Reservoir	13 Gallons
Fluid	Northland Talamar Extreme ISO 30
Cylinders	5 GPM Hi-Lo with 200 Mesh
Screen	Section Filter

CYCLE TIME

Item	Description
Time	18 Seconds 3 HP / 29 Seconds 1 HP

Shop all replacement parts at:

